




Manufacturer		Intermec	Intermec	Intermec	
Printer Model					
		EasyCoder PC4	EasyCoder PF8d (DT)	EasyCoder PF8t (TT)	
Physical Description			The EasyCoder PF8 printers are the ideal, straightforward replacement for EasyCode 91, 7422 and C4/PC4 printers	The EasyCoder PF8 printers are the ideal, straightforward replacement for EasyCode 91, 7422 and C4/PC4 printers	
Physical Characteristics	Height	167 mm (6.6 in)	116 mm - (6.53 in)	172 mm - (6.7 in)	
	Width	230 mm (9.1 in)	168 mm - (6.6 in)	226 mm - (8.8 in)	
	Depth	257 mm (10.2 in)	218 mm - (8.5 in)	285 mm - (11.2 in)	
	Weight	2.3 kg (5.1 lbs)	2 kg - (4.4 lb)	2.5kg - (5.5 lb)	
Printing Characteristics	Print resolution	203 or 300 dpi - (8 or 12 dots/mm)	203 dpi - (8 dots/mm)	203 or 300 dpi - (8 or 12 dots/mm)	
	Maximum Print Width	104 mm (4.1 in)	104 mm - (4.1 in)	104 mm - (4.1 in)	
	Maximum Print Length	8.1 in	1727 mm - (68 in)	200 dpi => 1727 mm - (68 in) 300 dpi => 900 mm - (35 in)	
	Nominal Print Speed	Up to 3 ips	Up to 4 IPS (101.6 mm/s)	Up to 4 IPS (101.6 mm/s)	
Media Characteristics	Maximum Label Width	114 mm (4.5 in)	118 mm - (4.6 in)	118 mm - (4.6 in)	
	Minimum Label Width	25 mm (1.0 in)	25 mm - (1 in)	25 mm - (1 in)	
	Maximum Roll Diam.	125 mm (5.0 in)	127 mm - (5 in)	127 mm - (5 in)	
	Maximum Ribbon Length	100 m (3900 in)	N/A	274.32 m - (10 800 in)	
	Ribbon core inner diameter	13 mm (0.5 in)	N/A	26 mm (1 in)	
Mechaninterface cardal Design	General Impression		Comparably sturdy double-wall plastic desktop printer featuring integrated double clamshell design	Excellent Media access with ribbon capacity equal to industrial printers	
	Material	Bottom	ABS Blend	ABS Blend	ABS Blend
		Center Section	N/A	N/A	N/A
		Covers	ABS Blend	ABS Blend	ABS Blend
		Front/back	ABS Blend	ABS Blend	ABS Blend
Mechanics	Mix Metal & ABS Blend	Mix Metal & ABS Blend	Mix Metal & ABS Blend		
Electronics					
Processor		16-bit	32-bit	32-bit	
Memory	Standard	512 K SRAM 1 MB Flash	8 MB SDRAM 4 MB FLASH	8 MB SDRAM 4 MB FLASH	
	Optional	256 K SRAM 1 MB Flash (1 cartridge slot)	N/A	1 GB Compact Flash	
Interfaces	Standard		RS-232 serial Parallel (Centronics) USB 1.1	RS-232 Serial Parallel (Centronics) USB 2.0	
	Optional		Ethernet WiFi	Ethernet WiFi	
	Ethernet Solution	EasyLAN External		EasyLAN External	EasyLAN External
		Internal/External	External Adapter	External Adapter	External Adapter
		Speed	10BaseT	100 BaseT	100 BaseT
Wireless	External adapter available	External Adapter availbale	External Adapter availbale		
Printer Language		Esim (EPL emulator)	Esim (EPL emulator)	Esim (EPL emulator)	
Standard Features		Self-Strip LTS	Real-time Clock (RTC)		
Optional Features		Thermal Transfer External keyboard Font and firmware upgrade cards	Cutter Self strip + Label Taken Sensor (LTS) External Keyboard External Rewinder	Cutter Real-time Clock (RTC) Self strip + Label Taken Sensor (LTS) 300DPI Compact Flash External Keyboard External Rewinder	
Manufacturer's Warranty (Printer / Printhead)		1 year / 3 months or 30 km	1 year / 3 months or 30km	1 year / 3 months or 30km	
List Price - 2008/Q1. (200 dpi / 300 dpi) [€ HT]		420 € (DT) - 504 € (TT) / 672 € (TT)	395 € (200 dpi / PN# PF8DA03000000)	495 € (200 dpi / PN# PF8TA03000000) 645 € (300 dpi / PN# PF8TA03001000)	
Network Option (Ethernet / WiFi) [€ HT]		199 € (Ethernet) WiFi through External supplier	199 € (Ethernet / PN# INT-225746001) WiFi through External supplier	199 € (Ethernet / PN# INT-225746001) WiFi through External supplier	

Remark: Specifications and features can be changed without prior notice