

Imprimantes Fixes Intermec - Gamme 2009



Domaine d'utilisation:	Bureau / A la demande	Commercial	Industriel			Production - 24h/24 - 7J/7
	PF8d/PF8t	PD41/PD42	PF2i	PF4i	PM4i (RFID en Option)	PX4i/PX6i
WiFi Interne 802.11b (option)	Non	Non	Oui	Oui	Oui	Oui
Impression: Largeur Maxi (cm)	10.41	10.56	5.58	10.56	10.56	11.17 / 16.73
Lageur Etiquettes Mini / Maxi (cm)	2.54 / 11.81	2.54 / 11.81	2.54 / 5.99	2.54 / 11.43	2.54 / 11.43	11.98 / 16.99
Résolution (DPI)	203 / 300	203 / 300	203	203 / 300	203 / 300	203 / 300 / 400
Vitesse d'Impression (In/sec Maxi)	4 / 2	6 / 4	8	8	8	12 / 9
Fontes résidente ajustables	5	15	15	15	15	15
Diametre Rouleau (mm)	127	212	212	212	212	212
Réenrouleur	Option	Option	Option	Option	Option	Option
Cutter	Option	Option	Non	Option	Option	Option
Mémoire (Standard)	8 Mo DRAM 4 Mo Flash	8 Mo SDRAM, 4 Mo Flash	16 Mo SDRAM, 4 Mo Flash	16 Mo SDRAM, 4 Mo Flash	16 Mo SDRAM, 4 Mo Flash	16 Mo SDRAM, 4 Mo Flash
Memoire Additionnelle	1 Go CompactFlash	16 Mo Flash, 1 Go CompactFlash	16 Mo Flash, 1 Go CompactFlash	16 Mo Flash, 1 Go CompactFlash	16MB Flash, 1 Go CompactFlash	16MB Flash, 1 Go CompactFlash
Interfaces (standard)	RS232, USB	RS232, USB, Parallèle ou ethernet	RS232, USB, Wand pour EasySet™	RS232, USB, Wand pour EasySet™	RS232, USB, ethernet	RS232, USB Ethernet
Interface Centronic Parallèle	En standard	En standard ou Ethernet	Interne (option)	Interne (option)	Interne (option)	Interne (option)
Carte Industrielle Entrée/Sortie	N/A	N/A	Interne (option)	Interne (option)	Interne (option)	Interne (option)
Ethernet	Externe (option)	En standard ou Parallèle	Interne (option)	Interne (option)	Interne (option)	Interne (option)
Structure du bati	Plastique	Metal	Fonte d'aluminium	Fonte d'aluminium	Fonte d'aluminium	Metal
Poids	1.2 / 2.3 kg	13.0 kg	5.4 kg	8.0 kg	12.1 kg	12.8 / 14.7 kg
Dimension (H x L x P) (cm)	11.6x16.7x21.8 17.2x22.6x28.4	27.4x26.9x45.2	17.7x19.3x39.6	17.7x24.3x40.3	26.11x29.7x54.3	23.8x27.4x48.2 23.8x33.5x48.2

