

PC4 Migration Quick Glance

EMEA

Printer Configuration(1)	Replaces	Printing Method/Media	Resolution (DPI)	Connectivity (standard)	Printer Language
PF8DA03000000	PC4*01000000 PC4*01010000 (1)	DT	203	Serial, Parallel & USB	ESIM (EPL)
PF8TA03100000 [NEW]	PC4*01100000 PC4*01110000 (1)	DT or TTR (12.7mm/0.5" core)	203	Serial, Parallel & USB	ESIM (EPL)
PF8TA03101000 [NEW]	PC4*01001000 PC4*01101000 PC4*01111000 (1)	DT or TTR (12.7mm/0.5" core)	300	Serial, Parallel & USB	ESIM (EPL)
PF8TA03000000	None	DT or TTR (25.4mm core)	203	Serial, Parallel & USB	ESIM (EPL)
PF8TA03001000	PC4*01001000	DT or TTR (25.4mm core)	300	Serial, Parallel & USB	ESIM (EPL)

(1) Field-installable options: Cutter, Self-Strip, Ethernet, 1GB Flash with RTC (PF8t only)

EU power cord p/n 226-000010-100

UK power cord p/n 226-000011-400

* = A, B, or C (PC4A, PC4B, PC4C)